

## TRI- BITU PROOF W

Bitumen emulsion waterproofing coating

### Description

Tri-Bitu Proof W brown / black liquid blend of selected bitumens is emulsified with water to give an easily applied protective coating.

**Tri-Bitu Proof W** dries to a black, tough waterproof coating which is also resistant to the passage of water vapour.

**The product is certified by National Research Center.**



### Uses

To act as a damp-proof membrane and vapour seal for concrete and masonry.

It can also be used as a protective coating for concrete below ground.

### Advantages

- Easy to apply by brush or any suitable tools.
- Economical in use.
- Water base.

### Technical Data @°25c

DISCRETIONS	VALUE
Color	Brown to Black – Viscous Liquid
Density	1.100 ± 0.1 gm/cm <sup>3</sup>
Touch Drying	15 minutes
Drying Time	1 hour @25 oC
Time between coats	Minimum 2 hours
Final setting time	24 hours
Full hardness	7 days
Re-coating time	18 - 24 hours
Min. Application temperature	10° C
Rate of use (theoretical)	2 – 3 m <sup>2</sup> / Kg depending on the surface condition

### Directions for use

#### Surface preparation:

Surfaces to be coated must be sound, clean and free of oil or grease.

If the surface is dusty, it may be primed with a coat of Tri-Bitu Proof W, diluted with an equal quantity of cool, clean water and allowed to dry.

#### Application:

**Tri-Bitu Proof W** may be applied by brush, or squeegee.

It is recommended that one or two coats should be applied, depending on the degree of protection required.

Allow a minimum of 2 hours between coats.

**Tri-Bitu Proof W** should be well stirred before use.

#### Factory & Head Office:

6 October City - 4th Industrial Zone - Al Oula Industrial Zone Plot No.: 14

Tel.: (002) 011 195 48267 - Sales: (002) 010 007 88817 - (002) 011 184 87597

Technical Support Call : (002) 011 184 87880 - Email: sales@tichem-eg.com

www.trichem-eg.com

## TRI- BITU PROOF W

Bitumen emulsion waterproofing coating

### Cleaning

Tri-Bitu Proof W may be removed from tools and equipment with water when it is wet. When dry **Tri-Bitu Proof W** may be removed with white spirit.

### Package

Available in 200Kg drums and 10 Kg, 15 Kg pails.

### Shelf Life

Has a shelf life of 12 months if stored under normal warehouse conditions

### Storage

Store in shade under normal warehouse conditions.

### Fire

Non flammable.

### Health and Safety

**Tri-Bitu Proof W** and white spirit should not come in contact with skin and eyes or be swallowed . ensure adequate ventilation . In case of contact with eyes rinse immediately with plenty of water and seek Medical advice.



#### Factory & Head Office:

6 October City - 4th Industrial Zone - Al Oula Industrial Zone Plot No.: 14  
Tel.: (002) 011 195 48267 - Sales: (002) 010 007 88817 - (002) 011 184 87597  
Technical Support Call : (002) 011 184 87880 - Email: sales@tichem-eg.com