

## TRI – RELEASE

Release agent for Stamped Concrete applications.

### Description

**Tri - Release** is a release agent in powder form for use in the stamped concrete floors applications to allow the clean release of texturing mould from the fresh concrete surface.

**Tri - Release** can be used with the same color of the color concrete floor hardener or can add color variation to the textured concrete floor surfaces, providing an attractive two-color look that is part of most pattern stamped concrete installations.



### Uses

**Tri - Release** is manufactured from carefully selected raw materials which include a blend of special chemicals, special additives to prevent adhesion between the texturing mould and the concrete floor surface and selective pigments.

### Advantages

- Excellent release for texturing tools.
- Color variation for textured concrete surfaces.
- Available in different colors

### Rate of use

0.25 – 0.5 kg/m<sup>2</sup>

### Directions for use

Spread **Tri - Release** over the surface of the freshly casted concrete floor after the **Tri- Color Hardeenr** has applied. Immediately put the texturing mould on the concrete surface and push hard to create the required texture on the concrete surface. Remove the texturing mould ensuring that the required texture is achieved. Leave the concrete floor for 24 hours. Then wash it with water to remove the excess **Tri - Release**

#### Factory & Head Office:

6 October City - 4th Industrial Zone - Al Oula Industrial Zone Plot No.: 14  
Tel.: (002) 011 195 48267 - Sales: (002) 010 007 88817 - (002) 011 184 87597  
Technical Support Call : (002) 011 184 87880 - Email: sales@tichem-eg.com

## **TRI – RELEASE**

Release agent for Stamped Concrete applications.

### **Cleaning**

Clean all tools and equipment immediately after use with Water.

### **Package**

Tri - Release is available in 20 kg bags

### **Shelf Life**

Shelf life is 12 months from manufacturing date, in a dry, covered storage area.

### **Storage**

Should be store in original closed container, avoid the direct sun light ousters. The storage temperatures (10 – 30) C° t.

### **Health and Safety**

While using the product, gloves and goggles should be worn. Splashes to skin or eyes should be washed with clean water, in case of prolonged irritation, seek medical advice.



**Factory & Head Office:**

6 October City - 4th Industrial Zone - Al Oula Industrial Zone Plot No.: 14  
Tel.: (002) 011 195 48267 - Sales: (002) 010 007 88817 - (002) 011 184 87597  
Technical Support Call : (002) 011 184 87880 - Email: sales@tichem-eg.com